

# A 70 HINGED PVC



## Transmittance

**$U_w \geq 0.9$  (W/m<sup>2</sup>K)**

Consult typology, dimensions and glass.

## Acoustic insulation

|                             |                   |
|-----------------------------|-------------------|
| Maximum glazing             | <b>42 mm</b>      |
| Minimum glazing             | <b>4 mm</b>       |
| Maximum acoustic insulation | <b>Rw = 46 dB</b> |

## Sightlines

|       |            |
|-------|------------|
| Frame | 70 mm      |
| Sash  | 70 / 80 mm |

## Maximum dimensions / Sash

### Window

|            |              |
|------------|--------------|
| Width (L)  | 360-1,300 mm |
| Height (H) | 450-2,300 mm |

### Balcony door

|            |              |
|------------|--------------|
| Width (L)  | 360-1,300 mm |
| Height (H) | 600-2,400 mm |

### Door

|            |              |
|------------|--------------|
| Width (L)  | 700-1,300 mm |
| Height (H) | 600-2,500 mm |

## Maximum weight / Sash

|                     |
|---------------------|
| 130 kg Window       |
| 130 kg Balcony door |
| 160 kg Door         |

## Certificates

DTA certification from CSTB lab.



## Categories achieved at test centre

Protection against atmospheric agents.

### Air permeability

**(UNE-EN 12207): Class 4**

### Water tightness

**(UNE-EN 12208): Class E1800**

### Wind resistance

**(UNE-EN 12210): Class C5**

\* Reference test 1.23 x 1.48 m / 2 sashes

Test verified by

**ALUMINIOS CORTIZO S.A.U.**

## Finishes

White  
Colour  
Bicolour  
Wood effect

## Opening possibilities

Inward opening: side hung, tilt & turn, tilt & parallel, bottom hung and bi-fold.

Outward opening: side hung and top hung.

